



* NOTE: All relevant materials are complied with RoHS directive .



	PCB: UTS-422/485 VER.B_C, W/IC: FT232BL+ADM3491ARZ	1	
6	PLASTIC HOOD COLOR TRANSPARENT	1set	
	MOLDED PVC BLACK		M304
5	MOLDED PVC BLACK		M304
4	USB CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, OD 5.0mm, JACKET BLACK, DRAWING No. EUAB2801P2402C-144	L-50mm	M304
3	HEX-NUT 4.75*8.5mm	2	
2	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR, PCB TYPE	1	
1	USB A MALE, GOLD FLASH ON CONTACTS/METAL HOOD, WHITE INSULATOR, SHORT A FIBRE TYPE	1set	M108
No.	DESCRIPTION	Q'TY	Supplier
APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~20mm ±10mm 201~1000mm ±20mm 1001~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
CHECKED	HU		
DRAWING	JUDY		
DATE	02/SEP/10	ITEM NO.	
		UNIT:mm	

P1	PCB
1	1 RED 24#
2	2 WHITE
3	3 GREEN
4	4 BLACK 24#
SHIELD	SHIELD