

USB to UART with +3.3V & +5V TTL Adapter thru AP Control

The USB to Serial UART (TTL level) adapter allows you to connect your computer through USB port and use it as a regular serial communication. All USB protocol is handled with this adapter thru AP control.

This adapter is perfect for embedded systems that require a serial connection to a computer. It shows up on any Windows computer as a standard serial COM port. Any application that talks to this COM port is automatically converting to USB and back to UART to your target unit.

Compatible with Windows 98SE / ME / 2000 / XP / Vista / 7 / 8 / 8.1 / 10 / [11](#); Win CE, Win Server 2003 / 2008 / 2008R2 / 2012 / 2012R2; Mac OS 8.6 / OS 9.x / OS 10.x, Linux Kernel 1.5.0 or higher.

Features

- Provides a USB to TTL Serial interface with various end connectors.
- Enables to configure +3.3V or + 5V thru application programmer
- All in one solution for USB to asynchronous serial data transfer interface
- UART interface supports for 7 or 8 data bits, 1 or 2 stop bits and odd / even / mark / space / no parity
- Fully assisted hardware (RTS#/CTS#) or X-On / X-Off software handshaking.
- Data transfer rates up to 3 Mbaud at TTL levels.
- Transmitting and receiving LED indicators.
- Supports +3.3V / 5V output to drive voltages optionally from +3.3V to +5V TTL inputs and delivers signal to target MCU

Specification

Model No.		UTS-TTL2VUI		
Chip		FTDI	6 Pin Header Pin Assignment	
USB Specification		USB 1.1 / 2.0 compliant	Pin 1	GND
Connector	Upstream	USB Type A Male	Pin 2	CTS
	Device	6 Pin Header	Pin 3	VCC (+3.3V or +5V)
Power Mode		Bus Powered	Pin 4	TXD
Cable Length		1.8m	Pin 5	RXD
Housing		Molding (PVC)	Pin 6	RTS

