

USB to UART with +3.3V TTL Adapter

The USB to Serial UART (TTL level) adapter allows you to connect your computer through USB port and use it as a regular serial communication. All USB protocol is handled with this adapter without application programmer.


This adapter is perfect for embedded systems that require a serial connection to a computer. It shows up on any Windows computer as a standard serial COM port. Any application that talks to this COM port is automatically converting to USB and back to UART to your target unit.

Compatible with Windows 98SE / ME / 2000 / XP / Vista / 7 / 8 / 8.1 / 10 / [11](#); Win CE, Win Server 2003 / 2008 / 2008R2 / 2012 / 2012R2; Mac OS 8.6 / OS 9.x / OS 10.x, Linux Kernel 1.5.0 or higher.

Features

- Provides a USB to TTL Serial interface with various end connectors.
- Entire USB protocol handled by the electronics in the cable USB
- All in one solution for USB to asynchronous serial data transfer interface
- UART interface supports for 7 or 8 data bits, 1 or 2 stop bits and odd / even / mark / space / no parity
- Fully assisted hardware (RTS#/CTS#) or X-On / X-Off software handshaking.
- Data transfer rates up to 3 Mbaud at TTL levels.
- +3.3V output allows external logic to be powered from the USB port
- Transmitting and receiving LED indicators.
- UHCI / OHCI / EHCI host controller compatible

Specification

Model No.		UTS-TTL3VT-AJ		
Chip		FTDI	Pin Assignment	
USB Specification		USB 1.1 / 2.0 compliant	Pin 1	TX
Connector	Upstream	USB Type A Male	Pin 2	RX
	Device	3.5mm Phone Plug	Pin 3	GND
LED		2		
Environment	Operating Temp.	0 °C ~ 40 °C		
	Storage Temp.	-20 °C ~ 60 °C		
	Humidity	0~80% RH, Non-condensing		
Power Mode		Bus Powered		
Cable Length		1.8m		
Housing		Molding (PVC)		

